



High Performance Safety Flooring

Recommended cleaning methods

Note: Do not use detergents containing pine oil

MACHINE



1 Sweep and/or vacuum up dust and other debris.



2 Load an approved detergent and dilute to manufacturer's recommendations.



3 Apply solution and allow to activate for approximately five minutes.
(Preferably using a mop & bucket).



4 If and when required machine scrub using synthetic brushes and/or blue pads.

5 Wet vacuum residue.

6 **Rinse thoroughly with hot, clean water to ensure that the surface PH of the flooring is neutral (PH 7).**

7 Wet vacuum.

8 Allow surface to dry before re-use.

Note: The use of a hand 'edge scrubber' may be necessary into corners to ensure complete floor coverage.

MANUAL



1 Sweep and/or vacuum dust and other debris.



2 Apply an approved detergent, diluted to manufacturer's recommendations.
Leave on floor for approximately five minutes.



3 If and when required scrub with deck scrubber.



4 Wet vacuum or mop residue.

5 **Thoroughly rinse with hot, clean water to ensure that the surface PH of the flooring is neutral (PH 7).**

6 Allow to dry.

safety without compromise...

explore **altroism** at www.asf.com.au

Safety Flooring

Some 'never do's' & helpful hints

Easyclean
TECHNOLOGY™



- Never polish or seal Altro safety flooring.
- Do not mix detergents.
- Wipe up spillages immediately.
- Use only approved detergents that do not contain pine oil, and have a PH of about 10.
- Use only the concentrations recommended by the manufacturer.
- If sudding occurs, add a dash of white vinegar to neutralise.
- Remove any oil or grease spillages before you start.
- Sweep the floor thoroughly before washing.
- When scrubbing use nylon brushes or blue pads for ALL grades of Altro safety flooring.
- When rinsing use hot, clean water and clean equipment, replacing water regularly and always use twin compartment buckets fitted with a ringer and ensure mops are clean.
- Remove any rubber heel marks by abrasion with a nylon brush and recommended detergent.
- Use quality equipment and machines whenever possible.
- Dirty equipment, particularly mops, do not clean – they merely redistribute the dirt.
- Do not accept new floors until satisfied that the initial clean has been thoroughly carried out.
- Cigarettes and oven hot objects will sear the surface of Altro safety flooring. Therefore, over side catchment trays and heat shields should be provided.
- New black rubber fittings may cause brown discolouration – particularly on new floors in strong sunlight. Such fittings can be lacquered to prevent this discolouration.
- Contact any ASF office or Technical Services for further advice.

safety without compromise...

explore **altroism** at www.asf.com.au